

## react

Posted February 22nd, 2024

react is a frontend javascript implementation

1. you can run react direct in a standard html file  
[https://www.w3schools.com/react/react\\_getstarted.asp](https://www.w3schools.com/react/react_getstarted.asp)
2. Or create a react.js app
  - npm install -g create-react-app
  - npx create-react-app my-app-name
  - npm start - will start app on port 3000
  - edit package.json to redirect port  
under scripts section in package.json  
change "start": "PORT=9561 react-scripts start",
  - this is a development version
  - can redirect apache with  
ProxyPass / http://localhost:9561/
  - the sample app created expects the app to be at the top level  
e.g. react.mindcontract.com  
The paths are not set up to allow a subdir app.

react.js cheatsheet

From facebook.

Babel transpiler translates react.js to html/css

Command that puts JSX on DOM

```
ReactDOM.render(JSX, document.getElementById('root'))
```

When defining a JSX must return a complete element

comments:

```
{/* comments here */}
```

ReactDOM api renders JSX to HTMLDOM

```
ReactDOM.render(componentToRender, targetNode)
```

use className instead of class on elements

Components:

1. components start with Capital letter
2. must return element or null
3. stateless

```
const MyComponent = function () {  
  return (  
    <div>foo</div>  
  )  
}
```

```
4. ES6 format - extend from React.Component  
class MyComponent extends React.Component {  
  constructor(props) {  
    super(props);  
  }  
}
```

```
render() {  
  return (  
    <h1>Hi</h1>  
  );  
}
```

```
const ChildComponent = () => {  
  return (  
    <div>hello</div>  
  );  
}
```

Composition

-----

Once you define a component, compose with `<NameComponent arg="foo" />`  
``${props.foo}` is the value.

```
import PropTypes from 'prop-types';
```

